

colorstuk rapid n (sanded grout)

colorstuk rapid n is a type CG 2 high-performance, cement-based grouting material as per EN 13888, for grouting joints from 1,5 to 16 mm - 1/16" to 5/8". Suitable for all kinds of ceramic tiles and natural stone, it is specially recommended for outdoor applications and permanently damp environments.

A high-tech, fine grained colored mortar with fast setting and hardening times for grouting tile joints from 1,5 to 16 mm - 1/16" to 5/8". Suitable for all kinds of ceramic tiles and natural stone. Indoors and outdoors.



- glass
mosaic
- rectified
ceramics
- high traffic
- bathroom
environments
- pools
- façades

colorstuk rapid n

Features:

- Cement-based, single-component, colored mortar.
- Sanded grout
- Fine texture mortar for grouting tile joints from 1,5 to 16 mm - 1/16" to 5/8".
- Mortar with fast setting and hardening times.
- It prevents efflorescences.
- Excellent mechanical resistance.
- Resistant to heat and UV radiation.
- Frost-resistant.
- Waterproof mortar.
- Anti-mold action.
- Easy to apply and clean.

Substrates:

- All usual substrates for ceramic tiles laying.

Recommended use:

- Tile joints from 1,5 to 16 mm - 1/16" to 5/8".
- Indoor wall and floor tiles.
- Outdoor floors and terraces.
- High traffic floor tiles.
- Floor tiles on radiant heating.
- Pools and damp environments.
- Outdoor wall tiles in façades.

Materials:

- Absorbent and non-absorbent ceramic tiles, including porcelain tiles.
- Tiles with mosaic-like patterns.
- Glass mosaic.
- Clay and terracotta tiles.
- Natural stone and marble not prone to staining.

Standards and approvals:

EN 13888 CG2 Ar W

Coverage

TILE SIZE	COLORSTUK RAPID					
	GROUT JOINT WIDTH					
	Coverages in sq.ft. (m ²) per 11 lbs. (5 kg)					
Width x Length x Thickness	1/16" (1.5875 mm)		1/8" (3.175 mm)		3/16" (4.7625 mm)	
	ft/bag	m ² /bag	ft/bag	m ² /bag	ft/bag	m ² /bag
1" x 1" x 1/4" (25x25x6 mm)	47	4.4	24	2.2	16	1.5
2" x 2" x 1/4" (50x50x6 mm)	94	8.7	47	4.4	31	2.9
3" x 3" x 1/4" (75x75x6 mm)	141	13.1	71	6.6	47	4.4
8" x 12" x 5/16" (200x316x8 mm)	345	32.1	173	16.1	115	10.7
12" x 12" x 3/8" (316x316x10 mm)	356	33.1	179	16.6	119	11.1
12" x 18" x 11/32" (316x446x9 mm)	464	43.1	232	21.6	155	14.4
12" x 23" x 11/32" (316x596x9 mm)	517	48.1	259	24.0	173	16.1
18" x 18" x 3/8" (446x446x10 mm)	503	46.7	251	23.4	168	15.6
12" x 35" x 3/8" (316x900x10 mm)	528	49.0	264	24.5	176	16.4
17" x 26" x 11/32" (435x659x11 mm)	538	50.0	269	25.0	179	16.7
23" x 23" x 11/32" (596x596x11 mm)	612	56.8	306	28.4	204	18.9
23" x 47" x 1/6" (596x1200x11 mm)	747	69.4	374	34.7	250	23.3
32" x 32" x 11/32" (800x800x11 mm)	828	76.9	411	38.2	275	25.5
7" x 26" x 11/32" (180x659x11 mm)	291	27.0	145	13.5	97	9.0
8" x 47" x 1/6" (193x1200x12 mm)	313	29.1	156	14.5	104	9.7



colorstuk rapid n

KEA	SAP	Color	Sample
B22501001	100004294	white	
B22502002	100004295	manhattan	
B22502003	100004296	bahama	
B22502004	100004297	cement	
B22502005	100004298	anthracite	
B22502006	100004299	black	
B22502007	100004300	caramel	
B22502008	100004301	terracotta	
B22502009	100004302	ivory	
B22502010	100004303	brown	
B22502011	100004304	tobacco	
B22502013	100004305	gray	
B22502016	100004308	beige	
B21522220	100060549	moka	
B22902002	100004309	black	

Colours shown are approximate. There are physical samples available to customers for checking the real grout colour.

Packaging

Presentation	Europallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
11 lb bag	880 lb/pallet
55 lb bag	2,200 lb/pallet