

CLEANING AND MAINTENANCE

3.-MAINTENANCE

a) Avoid stepping on the floor with footwear straight from the street (especially if it is wet or fouled with remains of grit, dirt or mud). We recommend the use of a doormat at the entrance to avoid remains of earth or gravel from entering the house. This recommendation is extended to all parts of the dwelling (galleries, terraces, etc.)

b) Certain types of footwear are not recommended (for example high heel shoes can mark the floor).

c) Avoid impacts of hard objects against the floor.

d) Place caps or felt under furniture legs to avoid scratching, especially in the case of heavy furniture. Take special care not to drag furniture when changing it from place to place.

e) Any liquid spilled on the floor must be cleaned up and dried immediately to prevent the fluid from seeping under the panels.

f) These products are subject to the climatic conditions of their surroundings, which entails constant exchange of moisture. This can cause dimensional changes (the material dilates when humid and shrinks when dry) and may cause deterioration unless a series of preventive measures are not implemented. Keeping the humidity in the house constant will help to mitigate extreme dilation and contraction of the wood and thus avoid bulging, warping, cracking and black stains. The product must be maintained within the recommended temperature and humidity ranges to get the best results:

A constant temperature of between 18 and 20 °C is suitable.

Relative humidity should be between 40% and 65% (limits accepted as healthy by the WHO (World Health Organisation)).

g) The aforesaid requires special conditioning: ventilation, heating and protection from direct sunlight.

h) Avoid exposing the floor to direct sunlight. Exposure to direct sunlight or strong artificial light will change the appearance of the floor in the long term.

i) Progressively heating to the desired temperature is recommended in the case of homes or apartments used in a temporary manner.

j) It is highly recommended to monitor these aspects carefully if the house will remain closed for long periods of time, taking special care to ensure suitable insulation.

k) Refrain from using grease, abrasive products, steel wool, wax or polish for cleaning and care. Avoid puddles of water from remaining on the floor. Steam cleaners are not suitable for use on laminate floors.

4.-CLEANING

Dry cleaning methods are recommended for day-to-day cleaning.

Dry cleaning: as a general rule cleaning the floor with a dry mop, soft broom or the vacuum cleaner will be sufficient. Grease stains or rubber sole marks can be cleaned with acetone.

Wet cleaning: we recommend wet cleaning the surface regularly depending on the degree of fouling. Dilute the Clean & Green Active detergent with water.



Flooring: AC4 LS 1L Ebano 24.3x220x0.8 cm.