

Model: AC5 CEMENT 1L GREY
Codes: 100244880 - L165004431
Group: G-222
Format: 23 21/32"X46 9/16"X5/16" approx.
Thickness: 5/16" approx.



ADDITIONAL NOTES

High resistance to water and moisture as long as the instructions for installation of this product for these cases are followed.

FEATURES

-  Beveled cut on all 4 edges of the board for emphasizing size
-  25 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Format where only one board has been used to finish the entire base surface
-  Floor capable of dissipating excess electrical charges and distribute them over its entire surface
-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  33. Intensive commercial
-  Suitable for floors in bathrooms and kitchens
-  Installation system where gluing the boards to the floor is not necessary. They are installed on a foam and joined together
-  5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.
-  Is suitable for installing on water radiant heating
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  23. Intensive residential
-  High quality decorative film laminate that simulates the aesthetics of cement floors, as well as floors with rust effects. Exclusive laminate for its aesthetics and piece format that simulates large-format ceramics.

DIMENSIONAL FEATURES

Item thickness	≤0.50 del valor nominal MM	UNE EN 13329:2016*
Length of face	Longitud≤1500 mm Δl≤0.5 mm	UNE EN 13329*
Width of face	Δs≤0.10 mm del valor nominal/max-min≤0.20 mm	UNE EN 13329*
Squareness of the item (q)	max≤0.20 mm	UNE EN 13329*
Straightness of face	max≤0.30 mm	UNE EN 13329*
Flatness of item (f)	Transversal: cóncava≤0.15%-convexa≤0.20%/Longitudinal: cóncava≤0.5%-convexa≤1%	UNE EN 13329*
Joint between items	Medio≤0.15 mm; max≤0.20 mm	UNE EN 13329*
Difference in height among items	medio≤0.10 mm; max≤0.5 mm	UNE EN 13329*
Dimensional variations related to changes in relative moisture	medio≤0.9 mm-max≤0.9 mm	UNE EN 13329*
Uv light fastness	Grado 4 en escala de grises	EN 20105-A02*
Punching	SIN CAMBIOS VISIBLES	EN ISO 24343-1*
Surface stripping	≥1.25	UNE EN 13329*

LABORATORY TESTS

Resistance to abrasion	AC5	UNE EN 13329*
Impact resistance	CLASE IC3	EN13329 tabla 2*
Resistance to staining	Grupo 1-2≥5/Grupo 3≥4	EN-438-2 / EN 13329*
Furniture leg effect	SIN DAÑOS VISIBLES	EN 424*
Castor chair effect	SIN DAÑOS VISIBLES	EN 425*
Swelling in thickness	≤10%	EN 13329*
Moisture upon leaving factory	Entre 4 Y 10%	
Formaldehyde emissions	E1	EN 712-2*
Slip resistance (cls)	Húmedo: Clase 1/Seco: Clase 3	UNE-ENV 12633*
Tensile strength of joints	F≥1 kN/ml	UNE EN 13329*
Fire resistance	Bfl-s1	EN 13501*
Evaluation of propensity to accumulation of electrostatic charges	≤2 kV	EN 1815*

PACKING

Boxes	22.96 SQF/CS	
Pallets	1561.2 SQF/PAL	
Units	7.65 SQF/ST	
Sale unit	M2	
Base unit	PIECES	
Net weight	19.83 LB/M2	
Gross weight	20.56 LB/M2	

SPECIAL PIECES

SAP	KEA	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100245113	L165004447	IGUALACION CEMENT 1L GREY 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100245116	L167013155	MAMPERLAN AC5 CEMENT 1L GREY 120X7X3	G-163	2 ST/CS	200 ST/PAL	11.9 ST/M2	ST	ST	1.58 KG/ST	1.64 KG/ST
100245143	L165004469	TRANSICION CEMENT 1L GREY 4X270X1	G-155	20 ST/CS	1000 ST/PAL	9.26 ST/M2	ST	ST	0.7 KG/ST	0.72 KG/ST
100245118	L165004455	ZOCALO CEMENT 1L GREY 8X220X1,5	G-107	14 ST/CS	560 ST/PAL	5.68 ST/M2	ST	ST	1.8 KG/ST	1.86 KG/ST

